


Other Related Products
 GT-10 Small Touch Screen

CIMREX High End HMI

Web Server (Ethernet)


* This can be used with the GT-30. With this unit, you can access both our PLC and the GT-30.

NEW Improved GT-30 V2 Touch Screen



New Features Lower Price!

- **New Drivers like Modbus RTU**
- **New Functions**
- **New Price**

**MSRP: \$699 Color
\$499 Mono**

The GT-30 has the smallest frame in the market and a very slim bezel. Take a look for yourself!

Slim and shallow case

While a lot of other 5.7" touch screens have big cases, we try to help you save panel space. The thin bezel and shallow case make the GT-30 one of the smallest touch screens in the industry.



Bright and wide viewing angle

33% brighter than VT-30



Wide 120 degree

The GT-30 is very bright and has an amazingly wide viewing angle. More than 120 degrees! This makes it really easy to operate your machine while increasing the productivity.

AIPT8001 (GTWIN software)


AFC1520M-US9
(Programming cable, 3m)



AFC1500GT-US (To MINI DIN5, 3m)
AFP15GT-US (To DB9, 3m)

Driver information

- ▶ Allen Bradley DF1 protocol
- ▶ **New** Modbus RTU
(supports AutomationDirect DL205, GE VersaNano)
- ▶ Aromat all FP PLC
- ▶ LG PLC
- ▶ Mitsubishi FX series PLC
- ▶ Omron PLC
- ▶ Siemens S7 PPI
- ▶ General Slave mode
([Download the protocol PDF](#))

Other Features

- ▶ **New** Trend Graph, Recipes
- ▶ **New** Alarm List, Password
- ▶ **New** Scaling
- ▶ Multi Languages
- ▶ 5x Quicker Response
- ▶ Large Memory
- ▶ True Type Font
- ▶ Custom Protocol
- ▶ Two Key Activation
- ▶ Pass Thru Programming
- ▶ Long Lasting Back Light
- ▶ Retentive Memory

Specifications

Screen	5.7"
Resolution	320 x 240 pixels
LCD	16 colors Blue (2 levels)
Back light	50,000 hours Replaceable
Memory	3.25MB (Color) 1.50MB (Mono) (160 pages)
Back light	50,000 hours Replaceable
Communication	RS232C (Up to 115.2Kbps)
Touch key res.	16 x 12
Language	English, Spanish, French, German, Italian, Japanese, Chinese, Korean
Dimension	158.2 x 126.8 x 45.5mm (W, H, D)
Panel cut out	139 x 67mm
Power	24Vdc, 0.45A
Rating	IP65
Conforming	CE UL, cUL(pending)

Order Information

AIPT3300B	GT-30 color
AIPT3100B	GT-30 Monochrome
AIPT8001	GTWIN software
AFC1520M-US9	Programming cable, 3m
AFC1500GT-US	3m cable between FP PLC and GT-30
AIPT380	Protective sheet, 10pcs*
AIPT381	Waterproof packing, 10pcs*
AIPT382	Back light*

* These come with the unit. These are the replacement parts